



Castrol Enduron 10W-40

Maximum oil drain & protection for diesel engines

Description

Castrol Enduron is a 10W-40 heavy duty diesel engine oil designed to allow fleet operators to run their vehicles to maximum oil drain intervals.

Application

Its primary application is for the latest Euro 4*, Euro 3 and Euro 2 European trucks and buses. It can also be used in off-road vehicles and equipment that require this performance level.

*Not for use in Euro 4 vehicles requiring low SAPS lubricants. For this application we recommend Castrol Enduron Low SAPS.

Advantages

Castrol Enduron 10W-40 uses advanced technology to provide excellent engine protection when used at maximum oil drain intervals, even under severe operating conditions. User benefits include:

- Maximum oil drain intervals to keep vehicles on the road for longer. The extra-strong additive system in Castrol Enduron 10W-40 keeps on working even in the toughest conditions. OEMs have approved Castrol Enduron 10W-40 for use at their maximum oil drain intervals.
- Engine protection, even when soot and other contaminants are present. Castrol Enduron 10W-40 protects against all types of engine wear, deposit build-up and bore-polishing. Its advanced formulation continues to protect even under the most severe conditions so extending engine life and preventing unscheduled downtime.

Typical Characteristics

Name	Method	Units	Castrol Enduron 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.866
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.4
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	87.2
Viscosity Index	ASTM D2270	None	155
Ash, Sulphated	ASTM D874	% wt	1.89
Total Base Number, TBN	ASTM D2896	mg KOH/g	16.1
Pour Point	ASTM D97	°C	-42
Flash Point, COC	ASTM D92	°C	232

Product Performance Claims

ACEA E4, E5, E7
API CF
MAN M 3277
MB-Approval 228.5
RVI RXD
Volvo VDS-3
Meets DAF extended drain requirements

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Enduron 10W-40
04 Sep 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk