



Castrol Transmax Multivehicle

Multivehicle Automatic Transmission Fluid

Description

Castrol Transmax Multivehicle is recommended for use in the automatic transmissions of a wide range of Japanese cars, light commercial vehicles and SUVs. It may be used in GM and Ford vehicles requiring Dexron III or Mercon fluids. Additionally it may be used in most European passenger Cars with 4 or 5 speed automatic transmissions.

Advantages

- Enhanced friction durability for smooth transmission performance.
- Exceptional high temperature protection to effectively resist fluid oxidation and the formation of deposits.
- Superb low temperature fluidity for cold weather shifting.

Typical Characteristics

Name	Method	Units	Transmax Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.848
Appearance	Visual	-	Clear & bright
Colour, Visual	Visual	-	Red
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.1
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	170
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	16000
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	220

Product Performance Claims

JASO 1A

Meets Mercon®

Dexron IIIH®

Recommended for use where:

- Toyota T, T II, T III, T IV, WS
 - Nissan Matic D, J, S
 - Mitsubishi SP II, IIM, III, PA, J3, SP IV
 - Mazda ATF M-III, M-V, JWS 3317, FZ
 - Subaru F6, Red 1
 - Daihatsu AMMIX ATF D-III Multi, D3-SP
 - Suzuki AT Oil 5D06, 2384K, JWS 3314, JWS 3317
 - Hyundai/Kia SP III, SP IV
 - Aisin Transmissions requiring JWS 3309
 - Honda/Acura DW 1/Z 1
 - Isuzu (where Toyota T-IV is required)
- is required.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Multivehicle

29 Nov 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn Bhd. (165875-W) Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8, Jalan Kerinchi, 59200 Kuala Lumpur
Phone No : 03-22818181 Toll free Line: 1-800-88-0018
www.castrol.com