



Transmax ATF FE Multivehicle

Automatic Transmission Fluid

Description

Castrol Transmax ATF FE Multivehicle is a lower viscosity, fully synthetic automatic transmission fluid designed for use in most modern Asian designed automatic transmissions to provide improved fuel efficiency. It is designed to meet the Japanese Automobile Standards Organisation performance needs (JASO 1A LV) and provide performance at least equal to Genuine automatic transmission fluids.

Advantages

- Provides outstanding slipping clutch durability for maximum fuel efficiency and shudder control performance – more than matches' genuine oil performance.
- Exceptional high temperature protection to effectively resist fluid oxidation that helps ensure excellent transmission cleanliness and durability.
- Enhanced friction durability for smooth transmission shift performance.
- Excellent shear stability helps ensure consistent high temperature performance.
- Superb low temperature fluidity for cold weather shifting.
- Excellent wear and corrosion performance to help ensure long transmission life.
- High torque capacity ensures strong performance in severe applications like towing and off-road applications.

Typical Characteristics

Name	Method	Units	Transmax ATF FE Multivehicle
Appearance	Visual	-	Clear & Bright
Colour	ASTM D1500	-	Red
Density @ 15C, Relative	ASTM D1298	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	6.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	29.5
Viscosity Index	ASTM D2270	None	156
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	208

Product Performance Claims

JASO 1A LV

Transmax ATF FE Multivehicle

17 May 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com