



## Transmax Manual Multivehicle 75W-90

Manual Transmission Fluid

### Application

Castrol Transmax Manual Multivehicle 75W-90, formulated with Smooth Drive Technology™, is a full synthetic transmission fluid recommended for most passenger car manual transmissions. Its superior technology enables longer transmission life. It is used successfully as a problem solver for low temperature shiftability issues and in the manual transmissions of a number of manufacturers as factory fill.

### Advantages

- Excellent synchroniser performance giving extended synchroniser life and shift comfort.
- Exceptional cold flow properties giving smoother gear shift at low temperatures.
- High shear stability giving a constant viscosity during oil life and noise reduction.
- Excellent thermal and oxidative stability for transmission cleanliness and longer oil life.
- Temperature reduction in operation prolongs the life of lubricant and aids fuel efficiency.

### Typical Characteristics

Name	Method	Units	Transmax Manual Multivehicle 75W-90
Density @ 15C	DIN EN ISO 12185	g/ml	0.873
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	15.09
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	76
Viscosity Index	ISO 2909	None	226
Viscosity, Brookfield @ -40C (75W)	DIN 51398	mPa.s (cP)	20000
Pour Point	ISO 3016	°C	-54
Flash Point, COC	ISO 2592	°C	190

## Product Performance Claims

API GL-4

MB-Approval 235.72

Meets Ford WSD-M2C200-C

\*SAE Class according to J306 pre 1998

Transmax Manual Multivehicle 75W-90

21 Jan 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)