



Product Data

ACRYLIC MOULD DRESSING

Issue Number 2
07/12/2000

Perspex Mould Release Agent

DESCRIPTION

Acrylic Mould Dressing is a specially formulated calcium soap based grease blended with low refined mineral oil containing a lubricity additive.

APPLICATION

Acrylic Mould Dressing is primarily used as a release agent during the moulding of acrylic materials such as perspex, and is usually applied on the surface of the mould prior to vacuum forming or blow moulding.

Acrylic Mould Dressing as been successfully used in the manufacture of aircraft cockpit canopies.

FEATURES

- ◆ Optimised formulation

BENEFITS

- ◆ Assists easy split from moulds

TYPICAL PHYSICAL CHARACTERISTICS

Worked Penetration	230
Drop Point °C	110

Health and Safety information sheets are available for all Castrol products from the address below:
**Castrol (U.K.) Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, England, Telephone:
Orders/Enquiries (08459)645111, Technical Enquiries (01793)452111, Fax (01793)491442**

1 of 1

All reasonable care has been taken to ensure that the information contained in this publication is accurate as at the date of printing. It should be noted however that the information above may be affected by changes occurring subsequent to the date of printing in the blend formulation or methods of application of any of the products referred to or in the requirements of any specification approval relating to any such products.