



Product Data

POWER1 Scooter 4T 5W-40

THE OIL THAT OFFERS OUTSTANDING PERFORMANCE AND PROTECTION.

Description

New Castrol POWER1 with 3-in-1 FORMULA is engineered to deliver outstanding performance and protection.

Application

Castrol POWER1 Scooter is suitable for scooters which require API SN (or lower) and JASO MB engine oils.

Advantages

Castrol POWER1 with the power of 3-in-1 FORMULA delivers:

- Excellent acceleration
- 3 meters ahead of a competitor's oil for bikes*
- Excellent protection
- Smooth riding

Complies with requirements of catalyst equipped engines

* Tested using 10W-40 oils in a Honda Activa 6G at wide-open throttle for 40 seconds from a rolling start. Acceleration benefits will be subject to riding style and oil viscosity grade.

Typical Characteristics

| Name | Method | Units | Castrol POWER1 Scooter 4T 5W-40 |
|---------------------------|------------|--------------------|---------------------------------|
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 88.7 |
| Pour Point | ASTM D97 | °C | -42 |
| Flash Point, PMCC | ASTM D93 | °C | 219 |
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.85 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 14.3 |
| Viscosity Index | ASTM D2270 | None | 167 |

Performance

API SN
JASO MB

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 Scooter 4T 5W-40

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com