



Iloform PN 226

Neat forming oil

Description

Castrol Iloform™ PN 226 is a medium viscosity, chlorinated and sulphurised, forming oil. It is specifically developed for medium to heavy duty deep drawing operations. It is a blend of high performance extreme pressure and boundary lubricants and anti wear additives, in a fully solvent refined paraffinic mineral oil.

Application

Iloform PN 226 is specially formulated for use in single die and progressive die presses for medium to heavy deep drawing applications. It is suitable for use on steels, stainless steels and nickel alloy steels

Advantages

- Formulated on solvent refined mineral oil. Does not contain hazardous aromatic constituents.
- Contains high performance extreme pressure, lubricity and anti wear additives. Maximises die life and provides excellent surface finish. Minimises costs associated with die repolishing.
- Excellent detergency. Removes metallic fines and particles from dies, eliminating defects associated with particulates. Improved surface finish, reducing scrap and rework costs.
- Relatively low viscosity, provides excellent cooling on high speed, multi stage operations, whilst minimising drag out, hence reducing product consumption.

Characteristics

Ester	Sulphur	Phosphorous	Chlorine	Other
✓	✓	✓	✓✓✓	✓

Typical Physical Characteristics

	Test Method	Unit	Value
Appearance	Visual	Visual	Hazy brown fluid
Viscosity @ 40°C	DIN 51562	mm ² /s	67
Viscosity @ 100°F	ASTM D446	[SUS]	310.6
Density @ 15°C	DIN 51757 ASTM D 1298	kg/m ³	1004
Density @ 60°F	Calculated	lbs/gal	8.378
Flashpoint	ISO 2592	°C	> 170
	ASTM D92	°F	> 338
Pour Point	ISO 3016	°C	
	ASTM D97	°F	
Copper corrosion	DIN 51 759 T1/ASTM D130	3 h at 100°C	

User Advice

Iloform PN 226 can be easily cleaned using mild alkaline or solvent cleaners.

Iloform PN 226
05 Sep 2016
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719
www.castrol.com/industrial