



Castrol Magnatec Diesel DX 5W-40

CLINGING MOLECULES PROTECT FROM THE START

Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oils drain off critical engine parts, however Castrol MAGNATEC's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection.

Castrol MAGNATEC's unique formulation protects from the moment you start, dramatically reducing* engine wear. Now with ultra-refined molecules, for protection you can see, hear and feel.

Castrol MAGNATEC. Instant Protection From The Moment You Start.

**As tested in the industry Sequence IVA wear test.*

Application

Castrol MAGNATEC Diesel DX 5W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C3, API SN/CF or earlier specification 5W-40 lubricant.

*GM dexos2®: supersedes GM-LL-B-025 and GM-LL-A-025 : GB2D0326082

Advantages

Castrol MAGNATEC's Intelligent Molecules also:

- Are combined with synthetic technology to provide increased protection in high and low temperature applications;
- Provide continuous protection for all driving conditions, styles and temperatures;

Castrol MAGNATEC Diesel DX 5W-40 delivers superior performance under extreme cold start up conditions compared to thicker grades.

Typical Characteristics

Name	Method	Units	Castrol Magnatec Diesel DX 5W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.4
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6220
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	81
Viscosity Index	ASTM D2270	None	169
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	207
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C3
API SN/CF
dexos2®*

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Magnatec Diesel DX 5W-40
31 Mar 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au