



Transmax ATF DX III Multivehicle

Automatic Transmission Fluid

Description

Transmax ATF DX III Multivehicle is recommended for use in GM automatic transmissions pre 2005 (Dexron® II or III) and Ford automatic transmissions built between 1983 and 1996 (Mercon®). This product is approved for use in Allison heavy duty transmissions against TES 389. It is also approved for use in a wide range of european heavy duty automatic transmissions.

NB: It can be used in some power steering units.

Advantages

- Multiple manufacturer approvals make it suitable for wide ranging use.
- It is specifically formulated for high thermal stability and resistance to oxidation which protects against the formation of deposits and oil thickening prolonging the life of components and lubricant.
- Optimised friction characteristics provide smooth shifting and efficient power transfer.
- High viscosity index provides a stable viscosity over a wide temperature range for effective protection of transmissions and operation of power steering units.

Typical Characteristics

Name	Method	Units	Transmax ATF DX III Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.859
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	175
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	16500
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	216

Product Performance Claims

Allison TES 389,
MAN 339 L1, MAN 339 V1, MAN 339 Z1,
MB-Approval 236.9,
Voith H55.6335.xx,
Volvo Transmission Oil 97341:071,
ZF TE-ML 04D, 14A
Meets Allison C4, Ford MERCON®, GM DEXRON®-IIIH, Volvo 97340

Additional Information

Transmax ATF DX III Multivehicle is registered under the following ZF approval number: ZF003368

Transmax ATF DX III Multivehicle
28 Jul 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk