

CRB Mini Truck 15W-40

For long and healthy engine life

Description

Castrol CRB Mini Truck 15W-40 with Heat Shield boosters, is specifically engineered to fight heat in your mini truck engine.

Mini Trucks are unique and different to big trucks, working in cities and subjected to special driving conditions. In fact in a typical working day a Mini Truck can run up to 25°C hotter* than a big truck. This excess can break down your engine oil, risking higher engine wear and harmful engine deposits which can lead to poor oil consumption.

Advantages

Castrol CRB Mini-Truck 15W40 with Heat Shield boosters, is engineered specifically to fight heat in your mini-truck engine.

Castrol CRB Mini-Truck 15W40 delivers:

- 3 times better heat protection**
- Exceptional protection from harmful deposits
- Helps maintain low oil consumption

*(based on field trial data Tata Ace vs. Tata 2516c)

** (In Industry oxidation testing CRB Mini Truck lasted three times longer than a conventional API CF-4 oil)



Typical Characteristics

Name	Method	Units	CRB Mini Truck 15W-40
Density @ 15C	ASTM D4052	g/ml	0.875
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.2
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	105
Viscosity Index	ASTM D2270	None	138
Ash, Sulphated	ASTM D874	% wt	1.2
Total Base Number, TBN	ASTM D2896	mg KOH/g	8.5
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	210

Product Performance Claims

API CH-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Mini Truck 15W-40

31 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com