



Transmax ATF/CVT Universal

Step Shifting & Continuously Variable Transmission Fluid

Description

Castrol Transmax® ATF/CVT Universal is a technologically advanced full synthetic formulation designed to deliver excellent performance in most of the traditional stepped automatic transmissions and Continuously Variable Transmissions currently in use. It is blended with premium base oils and an additive package which utilizes Castrol Smooth Drive® Technology. This is the first Castrol multi-vehicle ATF suitable for use in both step-shifting and continuously variable automatic transmissions. Transmax® ATF/CVT Universal is suitable for use in vehicles manufactured in North & South America, Europe, and Asia.

Advantages

- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Unsurpassed protection against copper corrosion
- Broad scope of vehicle applications improves workshop efficiency and inventory management

Typical Characteristics

Name	Method	Units	Transmax ATF/CVT Universal
Appearance	Visual	-	Clear & Bright
Colour	Visual	-	red
Density @ 15C, Relative	ASTM D4052	g/ml	0.849
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.1
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	34.2
Viscosity Index	ASTM D2270	None	179
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	9200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	214

Product Performance Claims

Suitable for use where Dexron VI, Ford Mercon LV, Ford Mercon V, Chrysler ATF +4, JASO 1A(03), JASO 1A LV(13) is required including: , Toyota T III, T IV, WS, Mitsubishi SP II, IIM, III, IV, PA, J3, Mazda ATF M-III, M-V, FZ, Honda/Acura DW 1/Z 1, Nissan Matic D, J, S, JWS 3314/3317/ 3309, Suzuki AT Oil 5D06, 2384K, Isuzu, Subaru F6, Red 1, Daihatsu AMMIX ATF D-III Multi, D3-SP, Hyundai/Kia SP III, SP IV, Also suitable for use in 6, 8 and 9-speed automatics from Audi, BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, VW, Porsche, 7 and 9 speed automatics from Mercedes Benz and all vehicles where Dexron III or Mercon SP is required.

Also Suitable for use where: , Toyota CVT Fluid TC, Toyota CVT Fluid FE, Nissan CVT Fluid NS-1, Nissan CVT Fluid NS-2, Nissan CVT Fluid NS-3, MMC DIAQUEEN ATF SP-III, MMC DIAQUEEN CVT Fluid J1, MMC DIAQUEEN CVT Fluid J4, MMC DIAQUEEN CVT Fluid J4+, Mazda CVTF 3320, Subaru i-CVT Fluid, Subaru i-CVT FG, Subaru Lineartronic High Torque Chain CVTF, Daihatsu AMMIX CVT Fluid DC, Daihatsu AMMIX CVT Fluid DFE , Suzuki CVT Fluid 3320, Suzuki CVT Fluid Green 1, Suzuki CVT Fluid Green 2, Suzuki CVTF TC, Suzuki NS-2, Honda HCF-2 * , Hyundai/Kia SP-III, Chrysler NS-2, Chrysler CVTF+4, Mini Cooper EZL799 , Ford CVT23, MB 236.20, all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch.

Transmax ATF/CVT Universal

20 Apr 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2

Plant Office:3660 Lakeshore Blvd West , Toronto, ON M8W 1P2 -

Phone 1-800-268-5339 Fax 416-252-7315 Plant Office telephone: 1 800 268-5339 Trade: 1 888 CASTROL Consumer: 1 800 CASTROL Technical Inquiries: 1 800 462-0835

E-mail info@wakefieldcanada.ca Website www.wakefieldcanada.ca www.castrol.com

Page: 2/2