



Product Data

Castrol MAGNATEC Stop-Start 0W-20

NON-STOP PROTECTION AND IMPROVED FUEL ECONOMY FROM EVERY START

Description

Busy driving, reinvented.

All cars, even those with the latest stop-start engine technology don't perform at their best in traffic congestion. And congestion has dramatically increased over the past 10 years, causing engine wear and wasting fuel.

That's why we created new Castrol MAGNATEC STOP-START, combining patented DUALOCK molecule technology with Castrol's most efficient full synthetic base oils.

Non-stop protection from every start, even for vehicles with modern stop-start engine technology.

Application

Castrol MAGNATEC STOP-START 0W-20 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP, ILSAC GF-6 or earlier specification 0W-20 lubricant.

Advantages

Castrol MAGNATEC STOP-START with DUALOCK Technology:

- Forms a powerful force-field of wear protection
- Dramatically reduces both warm-up¹ and stop-start² wear by 50%
- Could even deliver 50L annual fuel saving³ during busy stop-start driving
- MAGNATEC STOP-START 0W-20 is tested in Hybrid*

¹ Tested versus the Sequence IVA API wear limit.

² Tested versus the CEC OM646LA ACEA wear limits.

³ Compared to an industry reference 15W-40 oil in the EUDC cycle (for Highways), EPA NYCC (for cities) and Castrol Ultra-Idle Cycle (for congestion). Assumptions: Annual mileage of 12,000km; representative split of driving (60% on highway, 30% in city, 10% in congestion). Actual results under road conditions may vary according to vehicle type, driving conditions and style.

*Toyota Prius, EPA NYCC.

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC Stop-Start 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.846
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.6
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5600
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	45
Viscosity Index	ASTM D2270	None	171
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	200
Ash, Sulphated	ASTM D874	% w t	0.82

Product Performance Claims

API SP
ILSAC GF-6

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC Stop-Start 0W-20

09 Aug 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com