



Castrol MAGNATEC Diesel 10W-40 B4

Non-stop protection from every start.

Description

Clinging molecules, reinvented.

Traffic congestion has increased dramatically; today even a normal driver can stop and start up to 18,000 times¹ a year. That's annoying, but worse, it slowly damages your engine – permanently.

Castrol MAGNATEC Diesel contains dedicated diesel technology and breakthrough DUALOCK molecules that cling to critical engine parts and lock together to:

- Form a powerful force field of protection
- Dramatically reduce both warm-up² and stop-start³ wear by 50%
- Deliver unique protection designed specifically for modern driving
- Help maintain engine efficiency and responsiveness in common rail diesel engines
- Deliver excellent soot handling performance

Non-stop protection from every start.

¹ Global average from 50 cities, Castrol MAGNATEC STOP-START Index 2014

² Tested versus the Sequence IVA API SN wear limit.

³ Tested versus the CEC OM646LA ACEA wear limits.

Application

Castrol MAGNATEC Diesel 10W-40 B4 is suitable for use in automotive diesel and gasoline engines where the manufacturer recommends an ACEA A3/B4, A3/B3, API SN 10W-40 lubricant.

Castrol MAGNATEC Diesel 10W-40 B4 is approved for use in vehicles from leading manufacturers; please refer to the specifications section and your owners handbook.

Typical Characteristics

| Name | Method | Units | Castrol MAGNATEC Diesel 10W-40 B4 |
|---------------------------|------------|--------------------|-----------------------------------|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.868 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 14.6 |
| Viscosity, CCS -25C (10W) | ASTM D5293 | mPa.s (cP) | 6500 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 101 |
| Viscosity Index | ASTM D2270 | None | 150 |
| Pour Point | ASTM D97 | °C | -42 |
| Flash Point, PMCC | ASTM D93 | °C | 202 |
| Ash, Sulphated | ASTM D874 | % wt | 1.2 |

Product Performance Claims

ACEA A3/B3, A3/B4
API SN
Meets Fiat 9.55535-D2
MB-Approval 226.5
Renault RN 0700 / RN 0710
VW 501 01 / 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC Diesel 10W-40 B4
16 Apr 2021
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com