



Castrol Power Steering Fluid

Automatic Transmission & Power Steering Fluid

Description

Castrol Power Steering Fluid may be used in power steering units of many types of vehicle where Dexron IID or Mercon performance is required

Advantages

- Efficient operation of power steering units in all conditions.

Typical Characteristics

Name	Method	Units	Castrol Power Steering Fluid
Density @ 15C, Relative	ASTM D1298	g/ml	0.883
Colour	ASTM D1500	-	Red
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.1
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	45000
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	36
Viscosity Index	ASTM D2270	None	162
Flash Point, PMCC	ASTM D93	°C	180

Castrol Power Steering Fluid
11 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol K.K., East Tower 20F, Gate City Ohsaki, 1-11-2, Ohsaki, Shinagawa-ku, Tokyo 141-0032, Japan
Technical Advice Line: 03-5719-7777 Customer Service: 03-5719-7777
www.castrol.com