



Castrol GTX High Mileage 20W-50

Specially Formulated To Help Extend High Mileage Engine Life

Description

Castrol GTX is one of the world's most trusted engine oils.

It's more than just oil. It's liquid engineering that protects against high mileage problems, like smoke and leaks that your engine faces every day.

As engines age, seals can become brittle, allowing oil to leak through your engine, increasing oil consumption.

Help extend the life of your high mileage engine with Castrol GTX High Mileage.

Application

Castrol GTX High Mileage 20W-50 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SG/CD or earlier specification 20W-50 lubricant.

Advantages

Castrol GTX High Mileage:

- Engineered to protect against smoke and leaks
- Helps control oil consumption
- Seal friendly formulation preserves elasticity of engine seals
- Outstanding protection against engine wear

Typical Characteristics

Name	Method	Units	Castrol GTX High Mileage 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.884
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.4
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	6979
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	149
Viscosity Index	ASTM D2270	None	128
Pour Point	ASTM D97	°C	-27
Flash Point, PMCC	ASTM D93	°C	215
Ash, Sulphated	ASTM D874	% wt	0.7

Product Performance Claims

API SG/CD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX High Mileage 20W-50

08 Jan 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com