

**CRB Multi 15W-40**

For long and healthy engine life

**Description**

Castrol CRB Multi 15W-40 is a multipurpose engine oil, designed for use in a wide range of older generation commercial and heavy duty vehicles

**Application**

Castrol CRB Multi 15W-40 is recommended for use in BS I and BS II turbo charged trucks, tractors, mini-vans and jeeps, where API CF-4 performance is required.

**Advantages**

After a long working life, using the right oil is vital for older trucks to provide adequate protection against the build-up of problems within the engine. Castrol CRB Multi 15W-40 provides –

- Protection against oil thickening and deposit build up in critical engine parts
- Protection from wear and deposits
- Reduced maintenance cost and less downtime due to better engine protection

**Typical Characteristics**

Name	Method	Units	CRB Multi 15W-40
Density @ 15C	ASTM D4052	g/ml	0.886
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.4
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6050
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	106.4
Viscosity Index	ASTM D2270	None	138
Ash, Sulphated	ASTM D874	% wt	1.45
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.4
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	220

# Product Performance Claims

API CF-4

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Multi 15W-40

17 Apr 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India  
Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800  
Customer Service: [www.castrol.co.in](http://www.castrol.co.in) Email: [customercare.india@castrol.com](mailto:customercare.india@castrol.com)