



Tribol™GR CLS 000

Water-resistant Semi-fluid Grease

Description

Castrol Tribol™GR CLS 000 (previously called Olit™ CLS 000) is lithium/calcium based extremely water-resistant highperformance semi-fluid grease.

Excellent rheological properties in combination with an optimum low-temperature behavior ensures a wide range of applications.

Tribol GR CLS 000 grease features an excellent corrosion protection as well as a high resistance to detergents and caustic soda.

Application

- In central lubrication systems suited for semi-fluid greases.
- In gear units and gear motors lubricated with semi-fluid greases.
- Under unfavorable conditions (high humidity, in the presence of water)
- Temperature application range: - 40°C/- 40°F to + 100°C/+ 212°F

Advantages

- Excellently pumpable in centralized lubricating systems.
- Structurally stable - no blocking of the distributors by thickener residues.
- Extremely water-resistant.
- Resistant to detergents.
- Extraordinary corrosion protection.
- Very good low-temperature behavior.

Typical Characteristics

Name	Method	Units	Tribol GR CLS 000
Colour	Visual	-	Beige
Base oil	-	-	Mineral Oil
Thickener Type	-	-	Lithium - Calcium
Worked Penetration (60 strokes @ 25 °C/77 °F)	ASTM D217/ ISO 2137	0.1 mm	450 - 500
Density @20 °C/68 °F	Inhouse method	kg/m ³	900
Dropping Point	ASTM D566/ ISO 2176	°C/°F	150/300

Subject to usual manufacturing tolerances. * = Cannot be Determined.

Additional Information

Please observe the specifications of the bearing and plant manufacturers.

Tribol GR CLS 000 grease is miscible with lithium greases.

Maximum performance can be assured only if the product is not mixed with other lubricants.

This product was previously called Olit CLS 000. The name was changed in 2015.

Tribol™GR CLS 000

27 Jan 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial