



GTX 10W-40

GTX 10W-40

Description

Castrol GTX

Castrol GTX, with its unique shear stability viscosity improvers, exceeds demanding U.S. high shear and stay-in-grade requirements for viscosity breakdown protection. Rapid acceleration, sudden stops and high-revving all push your engine to work harder and run hotter. The extreme stress and soaring heat generated from this hard driving can shear and volatilize oil, leading to viscosity and thermal breakdown.

Application

Features and Benefits:

- The highest North American standard of protection against viscosity breakdown
- Advanced anti-wear additives to help extend engine life
- Superior detergency action to help prevent deposits

Conditions of Use

Warranty and Protection Requirements

- Exceeds engine manufacturer's warranty requirements for applications requiring API SN, SM and SL

Characteristics

Industry Specifications and OEM Approvals by Grade

Castrol GTX

Specifications:	5W-20	5W-30	10W-30	10W-40	20W-50
API SN	X	X	X	X	X
SM	X	X	X	X	X
SL	X	X	X	X	X
SJ	X	X	X	X	X
ILSAC GF-5	X	X	X		
ILSAC GF-4	X	X	X		
ILSAC GF-3	X	X	X		
Chrysler MS 6395	X	X			
Ford WSS-M2C153-H	X				
Ford WSS-M2C929-A		X			
Ford WSS-M2C930-A	X				
Ford WSS-M2C945-A	X				
Ford WSS-M2C946-A		X			
GM 6094*		X	X		

* meets performance

Typical Physical Characteristics

Typical Properties:

Castrol GTX

	Method	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity @ 100C, cSt	ASTM D445	9.1	10.7	11.3	14.3	17.0
Viscosity @ 210F, SUS	ASTM D2161	56.1	61.7	63.9	75.2	89.0
Viscosity @ 40C, cSt	ASTM D445	51.8	64.3	75.1	108	133
Viscosity Index	ASTM D2270	158	157	142	133	118
Low temperature (C) Cranking Viscosity, cP max	ASTM D5293	6,600 @ -30	6,600 @ -30	7,000 @ -25	7,000 @ -25	7,000 @ -25
Low temperature (C) Pumping Viscosity, cP max	ASTM D4684	40,000 @ -35	40,000 @ -35	50,000 @ -30	60,000 @ -25	60,000 @ -25
HT/HS Viscosity, cP min	ASTM D4683	2.6	2.9	2.9	2.9	3.0
Pour Point, F (C) max	ASTM D97	-44 (-42)	-38 (-39)	-22 (-20)	-27	-27
Flash Point, PMCC, C min	ASTM D93	>200	>200	>200	>200	>200
Density @ 15C, Relative	ASTM D4052	0.862	0.862	0.878	0.88	0.88
Pounds per Gallon		7.18	7.18	7.314	7.38	7.48

* Due to continual product research and development, the information contained herein is based on products purchased in and without notification. Typical properties may vary slightly.

Part Numbers and UPC's:

Packaged Goods

SAE Grades	5W-20	5W-30	10W-30	10W-40	20W-50
Case Size	12/1 Qt	12/1 Qt	3/1 Gal	12/1 Qt	3/1 Gal
Case Part #	12107	12082	3615	12092	3610
Bottle/Unit UPC	0-79191-00107-3	0-79191-00082-3	0-79191-00858-4	0-79191-00092-2	0-79191-00856-0
Case UPC	0-79191-12107-8	0-79191-12182-8	0-79191-03316-6	0-79191-12092-7	0-79191-03856-7

Bulk/Drum

SAE Grades	5W-20	5W-30	10W-30	10W-40	20W-50
Unit Size	55 gal drum	Bulk	55 gal drum	Bulk	55 gal drum
Part #	550940075	0084	0080	0094	0090

Recommended Concentrations

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

GTX 10W-40

31 Oct 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com