



Product Data

Transmax CVT

CVT Fluid

Description

Castrol Transmax CVT, formulated with Smooth Drive Technology™, is a full synthetic fluid for use in continuously variable transmissions (CVT) of most passenger cars. Its superior technology enables longer transmission life. It can be recommended for use in most passenger cars fitted with push belt or chain technologies. Castrol Transmax CVT, formulated with Smooth Drive Technology™, provides higher torque capacity and enhanced wear protection, extending the fluid performance and giving drivers a smoother drive for longer.

Advantages

- Higher torque capacity
- Enhanced wear protection in the push belt–pulley interface
- Superior operational efficiency with reduced risk of belt-slippage
- Improved oxidative stability with excellent viscosity control

Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15°C	ASTM D4052	g/ml	0.849
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7.1
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	34
Viscosity Index	ASTM D2270	None	179
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	9200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	214

Performance

Suitable for use where the following are called for: Toyota CVT Fluid TC, FE

Nissan CVT Fluid NS-1, NS-2, NS-3

MMC DIAQUEEN ATF SP-III, CVT Fluid J1, CVT Fluid J4, CVT Fluid J4+

Mazda CVTF 3320, Subaru i-CVT Fluid, i-CVT FG, Lineartronic II

Lineartronic High Torque Chain CVTF

Daihatsu AMMIX CVT Fluid DC, CVT Fluid DFE

Suzuki CVT Fluid 3320, Green 1, Green 2, CVTF TC, NS-2

Honda HCF-2 *

Hyundai/Kia SP-III, SP-CVT 1

Chrysler NS-2, CVTF+4

Mini Cooper EZL799

Ford CVT23

MB 236.20

VW/Audi TL 52180 (G 052 180), TL 52516 (G 052 516)

Dex CVT

Suitable for use in Perodua where Perodua CVT Fluid or CVT FE is required.

*Transmax CVT is suitable for use in all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch.

Transmax CVT

26 Oct 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com