



Product Data

Transmax ATF Dex/Merc Multivehicle

Multivehicle Automatic Transmission Fluid

Description

Castrol Transmax ATF Dex/Merc Multivehicle is recommended for use in GM and Ford vehicles requiring Dexron III or Mercon fluids and the automatic transmissions of a wide range of Japanese cars, light commercial vehicles and SUVs . Additionally it is suitable for use in most European passenger Cars requiring a Dexron III/Mercon fluid.

Advantages

- Enhanced friction durability for smooth transmission performance.
- Exceptional high temperature protection to effectively resist fluid oxidation and the formation of deposits.
- Superb low temperature fluidity for cold weather shifting.

Typical Characteristics

Name	Method	Units	Transmax ATF Dex/Merc Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.851
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.4
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	185
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	16000
Pour Point	ASTM D97	°C	-51
Flash Point, PMCC	ASTM D93	°C	200

Product Performance Claims

Meets Dexron®-IIIH, Mercon®
Suitable for Use as Power Steering Fluid
Suitable for use where JASO 1A(03)
JASO 1A LV(13) is required including:
Toyota T III, T IV
Mitsubishi SP II, IIM, III, IV, PA, J3
Mazda ATF M-III, M-V
Honda/Acura Z 1
Nissan Matic D, J
JWS 3314/3317/ 3309
Suzuki AT Oil 5D06, 2384K
Isuzu
Subaru F6
Red 1
Daihatsu AMMIX ATF D-III Multi, D3-SP
Hyundai/Kia SP III

Transmax ATF Dex/Merc Multivehicle

31 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com