



Contractor Special 2

Lithium Complex EP Grease

Description

Castrol Contractor's Special is a lithium complex grease with extreme pressure additives containing 3% Molybdenum Disulfide. Castrol Contractor Special is formulated to offer high temperature and heavy-duty performance coupled with good pumpability for applications where a tough durable lubricating film is needed. Castrol Contractor 's Special delivers better productivity and less downtime where "boundary lubrication" exists while extending lubricant usage, longer equipment life, and reduced lubrication frequency.

Advantages

Castrol Contractor's Special delivers:

- Superior film strength and anti-wear package with a high load capability
- Excellent pumpability for automatic systems
- 3% Molybdenum Disulfide to reduce friction
- High dropping point

Castrol Contractor Special is suitable for heavily loaded equipment such as bulldozers, shovels, loaders & off-highway trucks. Applications include plain and anti-friction bearings, ball joints, king pins, hinge and bucket pins, and heavy-duty chassis lubrication.

Typical Characteristics

Test	Method	Data
NLGI Grade	ASTM D 217	2
Thickener	-	Lithium Complex
Texture	visual	Tacky / Smooth
Color	visual	Gray
Penetration, Worked 60 strokes	ASTM D 217	265 - 295
Dropping Point °C/F	ASTM D 2265	min 260 / 500
4-Ball Weld Load, kg	ASTM D 2596	400
Load Wear Index	ASTM D 2596	50
4-Ball Wear Scar, mm	ASTM D 2266	0.39
Timken OK Load, lbs	ASTM D 2509	50
Water Sprayoff @ 100F	ASTM D 4049	27
Rust Prevention (Steel corrosion)	ASTM D 1743	Pass
Mobility, grams per min @ 77F	US Steel	552
Mobility, grams per min @ 60F	US Steel	300
Mobility, grams per min @ 40F	US Steel	110
Mobility, grams per min @ 20F	US Steel	41
Mobility, grams per min @ 0F	US Steel	6
Copper Corrosion	ASTM D 4048	1b
Solid Lubricant content in %	-	3

Contractor Special 2

12 Dec 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com