



Product Data

Performance™ Bio HE 32 TG

Biodegradable hydraulic oil

Description

Castrol Performance™ Bio HE 32 TG (previously called Castrol Carelube™ HTG 32) is a biodegradable hydraulic fluid formulated using vegetable ester oil and additives to prevent corrosion, wear, and oxidation.

Application

Performance Bio HE 32 TG is recommended for use where leakage or spillage may present a risk of harm to the environment or in environmentally sensitive areas such as waterways, agriculture, forestry, and mining and construction industries. It can also be used in metalworking applications where excellent lubricity is necessary such as in cutting and deformation processes especially for steel and non ferrous materials. Performance Bio HE 32 TG is miscible with conventional mineral oilbased fluids but in order to maximise the performance benefits of these products it is recommended to minimise residues of other lubricants in the lubrication system through draining or flushing.

Performance Bio HE 32 TG is classified as meeting the requirements of ISO 6743/4 - HETG and DIN 51524 Part 4 specifications. It also demonstrates superior biodegradation performance in accordance with the CEC-L-33-A-93 and OECD 301B test methods.

Advantages

- Extremely high viscosity index (VI) & excellent thermal stability ensures lubrication and protection over a wide temperature range.
- Rapidly biodegradable ensures accidental leaks or spills have a reduced impact on the environment.
- Excellent lubricity, anti-corrosion and anti-wear characteristics prolongs machine life and reduces maintenance costs.
- Naturally good shear stability and a longer service life compared with other vegetable oil based hydraulic fluids.

Typical Characteristics

Name	Method	Units	Performance Bio HE 32 TG
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	921
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	36
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	8.2
Viscosity Index	ISO 2909 / ASTM D2270	-	>200
Biodegradability	OECD 301B	%	75
Biodegradability	CEC-L-33-A-93	%	99
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	>270/>518
Pour Point	ISO 3016 / ASTM D97	°C/°F	-33/-27
Water Separation @ 54°C / 129°F (40/37/3)	ISO 6614 / ASTM D1401	min	15
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	30/0
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	-	Pass
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>12
Eaton-Vickers 35VQ/25 Vane Pump test (3000 psi, 2400 rpm, 100 hrs, 95°C / 203°F)	-	wt loss (ring & vane) mg	<5

Subject to usual manufacturing tolerances.

This product was previously called Carelube HTG 32. The name was changed in 2015.

Performance™ Bio HE 32 TG

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html