



Castrol Transmax Dex/Merc

Automatic transmission and power steering fluid

Description

Castrol Transmax™ DEX/MERC is a mineral based product which was originally designed for pre 1993 automatic transmissions fitted to Ford & General Motors vehicles.

Due to its inherently high viscosity index it is specified for many industrial and offshore applications where Dexron IID or Mercon performance is required.

Typical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	32
Viscosity at 100°C, cSt	ASTM D-445	7.2
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	17,000
Pour Point, °C (°F)	ASTM D-97	-43(-45)
Flash Point, °C (°F)	ASTM D-92	177(350)
Specific Gravity, 60°F	ASTM D-1298	0.863
Pounds per Gallon	ASTM D-287	7.19

These figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Dex/Merc
24 May 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Australia Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1825

Dubai City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

Norway Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43 501

Singapore Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

United Kingdom BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Arnhall Business Park, Westhill. AB32 6FJ, UK.
Customer Service Number +44 (0)1224 270365

USA 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157., Brazil Avenida Itaoca, 2.400, Inhauma, Rio de Janeiro, Zip code 21061-020, customer service +55 11 4133 7835