



Castrol Magnatec Diesel 15W-40

CLINGING MOLECULES PROTECT FROM THE START

Description

Castrol MAGNATEC DIESEL combines dedicated diesel technology with intelligent molecules for an extra layer of protection, reducing wear during the critical warm-up period.

Its unique formulation protects from the moment you start, dramatically reducing* engine wear. Now with ultra-refined molecules, for protection you can see, hear and feel.

**As tested in the industry Sequence IVA wear test*

Application

Castrol Magnatec Diesel 15W-40 is suitable for use in automotive diesel engines where the manufacturer recommends API CF or ACEA A3/B3, A3/B4 or earlier specifications including: TDI, DI, Inter-cooled, Turbo charged engines, Crdi engines that require a 15W-40 lubricant

Advantages

Castrol MAGNATEC DIESEL is always ready to protect:

- Dedicated diesel technology maintains engine efficiency and responsiveness in common rail diesel engines
- Providing excellent soot handling performance thus minimizing oil thickening

Typical Characteristics

Name	Method	Units	Castrol Magnatec Diesel 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.876
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	115
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6600
Viscosity Index	ASTM D2270	None	134
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	1.2

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF

Castrol Magnatec Diesel 15W-40

10 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com