

## Castrol Magnatec Professional 10W-40

Instant protection from the moment you turn the key

### Description

Castrol Magnatec Professional's intelligent molecules protect from the moment you turn the key. They cling to the engine like a magnet providing an extra layer of protection, dramatically reducing\* engine wear.

Castrol Magnatec Professional's unique formulation delivers protection you can see, hear and feel. With micro filtration technology it's engineered for today's modern engines.

Castrol Magnatec Professional. Instant protection from the moment you turn the key.

*\* As tested in the industry Sequence IVA wear test*

### Application

Castrol Magnatec Professional 10W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SM/CF or earlier specification 10W-40 lubricant. Castrol Magnatec Professional 10W-40 is recommended by TATA Motors.

### Advantages

Castrol Magnatec Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down
- Cling to your engine forming an extra layer that protects from the moment you turn the key;
- Bond to metal surfaces to make engine parts more resistant to wear;
- Provide continuous protection for all driving conditions, styles and temperatures.

## Typical Characteristics

Name	Method	Units	Castrol Magnatec Professional 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.867
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.2
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	5700
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	98
Viscosity Index	ASTM D2270	None	149
Pour Point	ASTM D97	°C	-36
Ash, Sulphated	ASTM D874	% wt	1.0
Flash Point, PMCC	ASTM D93	°C	195

## Product Performance Claims

API SM/CF

Recommended by TATA

Castrol Magnatec Professional 10W-40

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: [www.castrol.co.in](http://www.castrol.co.in) Email: [customercare.india@castrol.com](mailto:customercare.india@castrol.com)