



PRODUCT DATA

Castrol Contractor's Special

Castrol Contractor's Special is a lithium complex grease with extreme pressure additives containing 3% Molybdenum Disulfide. Castrol Contractor Special is formulated to offer high temperature and heavy-duty performance coupled with good pumpability for applications where a tough durable lubricating film is needed. Castrol Contractor 's Special delivers better productivity and less downtime where "boundary lubrication" exists while extending lubricant usage, longer equipment life, and reduced lubrication frequency.

Features and Benefits

Castrol Contractor's Special delivers:

- Superior film strength and anti-wear package with a high load capability
- Excellent pumpability for automatic systems
- 3% Molybdenum Disulfide to reduce friction
- High dropping point

Castrol Contractor Special is suitable for heavily loaded equipment such as bulldozers, shovels, loaders & off-highway trucks. Applications include plain and anti-friction bearings, ball joints, king pins, hinge and bucket pins, and heavy-duty chassis lubrication.



Typical Properties*

	Method	1	2
NLGI Grade			
Thickener-Type		Lithium Complex	Lithium Complex
Color		Gray	Gray
Appearance		Smooth-Tacky/Stringy	Smooth-Tacky/Stringy
Penetration, Worked @ 77°F	D217	329	285
Dropping Point, °F	D2265	530	550
4-Ball EP Weld Point	D2596	400	400
Load Wear Index	D2596	55	54
4-Ball Wear Scar, mm	D2266	0.4	0.39
Timken OK Load	D2509	50	50
Mobility-g/Min. 77°F	USS	696	552
Mobility-g/Min., 60°F		400	300
Mobility-g/Min., 40°F		180	110
Mobility-g/Min., 20°F		71	41
Mobility-g/Min., 0°F		15	6
Water Sprayoff @ 100°F	D4049	45	27
Base Oil Viscosity, SSU@100°F	D445	700	2710
Base Oil Viscosity, SSU@210°F	D445	70	188
Base Oil Viscosity, cSt@40°C	D445	151	511
Base Oil Viscosity, cSt@100°C	D445	13	39
Rust Prevention	D1743	Pass	Pass
Copper Corrosion	D4048	1B	1B

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

Part Numbers and UPCs

NLGI Grade	1	2
10 X 14 oz CTG Case Part No.	57713	57723
35 LB Pail Part No.	57717	57727
120 LB Keg Part No.	57718	57728
400 LB Drum Part No.	57719	57729
Bulk	57710	57720



Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: 1,800.462.0835
Email: contactus@bp.com
©2011 BP Lubricants USA Inc. All rights reserved.

www.castrol.com/us