

Castrol GTX T 0W-20

Superior sludge protection to help extend engine life

Description

Castrol GTX is one of the world's most trusted engine oils.

It's more than just oil. It's liquid engineering that protects against the problems your engine faces every day.

Severe driving conditions can cause the build up of a thick, tar-like substance called sludge. Sludge can block your engine's vital oilways like cholesterol – and if untreated it can rob an engine of power and, ultimately, its life.

Castrol GTX Double Action formula cleans away old sludge*, and protects against new sludge formation better than tough industry standards.

* Vs ACEA C2 Industry Standards

Application

Castrol GTX T 0W-20 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C2 0W-20 lubricant.

Advantages

Castrol GTX T 0W-20 provides:

- Provides superior protection against engine sludge*
- Advanced protection against viscosity and thermal breakdown.
- Premium quality base oils and anti wear additives to help extend the life of your engine.
- Helps minimize oil consumption

Typical Characteristics

Name	Method	Units	Castrol GTX T 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.8458
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	9.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44
Viscosity Index	ASTM D2270	None	200
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	0.7
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	6016

Product Performance Claims

ACEA C2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX T 0W-20

31 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com