

POWER1 Ultimate Sports Bike 15W-50

Outstanding Performance

Description

With so many engine oils available in the market, don't you want to know which one offers uncompromising performance?

Castrol POWER1 ULTIMATE with Full Synthetic is engineered for outstanding performance across 5 critical areas.

Castrol POWER1 ULTIMATE's 5-in-1 formula delivers outstanding performance and acceleration.

Application

Castrol POWER1 ULTIMATE 5W-40, 10W-40, 10W-50, 15W-50 and 20W-50 are suitable for all makes of 4-stroke bikes, both carburetor or fuel injected where API SN (or below) and JASO MA or MA2 are recommended.

Advantages

- Full Synthetic 4-stroke motorcycle engine oil
- Castrol POWER1 Ultimate's 5-in-1 formula delivers:
 1. Excellent acceleration*
 2. Excellent protection
 3. Smooth riding
 4. Keeps the engine cool on long rides
 5. Enduring performance
- Complies with requirements of catalyst equipped engines

*Acceleration benefits will be subject to riding style and oil viscosity grade.

Typical Characteristics

| Name | Method | Units | Castrol POWER1 Ultimate Sports Bike 15W-50 |
|---------------------------|------------|--------------------|--|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.8567 |
| Appearance | Visual | - | Clear & Bright |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 17.2 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 120 |
| Viscosity Index | ASTM D2270 | None | 157 |
| Pour Point | ASTM D5950 | °C | -36 |
| Flash Point, PMCC | ASTM D93 | °C | 206 |

Product Performance Claims

JASO MA2

“Suitable for 2-wheelers where API SN and below (SM/SL/SJ/SG) and JASO MA/MA2 is required.”

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 Ultimate Sports Bike 15W-50

04 Aug 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn. Bhd., Registration No. 198701007157 (165875-W), Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8, Jalan Kerinchi, 59200 Kuala Lumpur
Phone No : 03-22818181 Toll free Line: 1-800-81-6530
www.castrol.com