



Castrol Activ 4T10W-40

Continuous Protection

Description

The engine in your bike risks damage all the time, when starting up, when running and even when the engine is off.

New Castrol Activ 4T with Actibond™ molecules clings to the engine to provide 3X protection: through start-up, while the engine is running, and when the engine is off

Application

Castrol Activ 4T 10W-40 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and/or JASO MA2 and MA specifications are recommended.

Advantages

New Castrol Activ 4T delivers 3X protection*

Castrol Activ 4T contains Actibond™ molecules that cling firmly to the engine parts:

Castrol Activ 4T:

- Provides 50% better** wear protection during start-up
- Fights deposits and provides superior engine cleanliness during running
- Provides excellent corrosion protection, even when the engine is off

*Protection in 3 stages of the ride: through engine start-up, running, and while the engine is off.

**vs reference API SL oil in Sequence IVA test

Typical Characteristics

Name	Method	Units	Activ 4T 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.867
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	100
Viscosity Index	ASTM D2270	None	149
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	212

Product Performance Claims

API SL
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T10W-40
13 Mar 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com