



Castrol GTX Professional Diesel 5W-30

Superior protection against harmful engine deposits

Description

Castrol GTX Professional is one of the world's most trusted motor oils. It's more than just oil. It's liquid engineering ~~to clean away and protect against harmful engine deposits~~

~~Castrol GTX Professional Diesel~~ that provides extra protection against engine problems, like soot and harsh deposits that your engine faces every day.

Why is this important? Because soot and harsh deposits can make the oil thicker; blocking oil ways, causing wear and decreasing performance.

[Help extend the life of your engine with Castrol GTX Professional Diesel](#)

Application

Castrol GTX Professional Diesel 5W-30 is suitable for use in automotive diesel engines where the manufacturer recommends an ACEA A5/B5 5W-30 lubricant.

Castrol GTX Professional Diesel 5W-30 is suitable for use in Maruti Suzuki diesel engines that require a 5W-30 lubricant.

Advantages

Castrol GTX Professional Diesel helps extend the life of your engine:

- Superior cleaning power to maintain engine performance
- Reduces the build up of harsh deposits
- Helps prevent oil from thickening and keeps it flowing freely
- Outstanding diesel engine wear protection
- Suitable for inter-cooled, Turbo charged diesel engines
- Micro filtered and engineered for today's modern engines

Typical Characteristics

Name	Method	Units	Castrol GTX Professional Diesel 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.4
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5200
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	65
Viscosity Index	ASTM D2270	None	170
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	207
Ash, Sulphated	ASTM D874	% wt	1.2

Product Performance Claims

ACEA A5/B5

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Professional Diesel 5W-30

18 Mar 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com