



## Transmax Limited Slip 75W-90

Axle Fluid for limited slip differentials

### Description

Castrol Transmax Limited Slip 75W-90 is a full synthetic high performance SAE 75W-90 gear lubricant, specifically developed for highly loaded limited-slip axles of modern vehicles. It is also applicable for other axles and certain manual gearboxes, if API GL-5 performance level is recommended by the manufacturers

### Advantages

- Excellent anti-wear and extreme pressure performance at all ambient temperatures and load conditions provide better final drive protection leading to longer life and reduced repair costs.
- Excellent cold flow properties reduces torque loss and increases efficiency and ensures improved protection at start up in cold conditions.
- Excellent thermal and oxidative stability combined with operating temperature reduction.
- Excellent shear stability permitting longer oil and component life.

### Typical Characteristics

Name	Method	Units	Transmax Limited Slip 75W-90
Density @ 15C	DIN EN ISO 12185	g/ml	0.859
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	15.5
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	102
Viscosity Index	DIN ISO 2909	None	160
Viscosity, Brookfield @ -40C (75W)	DIN 51398	mPa.s (cP)	58400
Pour Point	DIN-ISO 3016	°C	-51
Flash Point, COC	ISO 2592	°C	226

### Product Performance Claims

API GL-5 limited slip performance. Approved for use in Voith final drive units and listed in 132.00374402 and 132.00374401 Voith's recommended lists.

Transmax Limited Slip 75W-90  
02 Jun 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)