



Castrol MAGNATEC Diesel 5W-40 DPF

CLINGING MOLECULES PROTECT FROM THE START

Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oils drain off critical engine parts, however Castrol MAGNATEC Diesel 5W-40 DPF's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection.

Castrol MAGNATEC Diesel 5W-40 DPF's formulation protects from the moment you start, dramatically reducing* engine wear, for protection you can see, hear and feel.

Castrol MAGNATEC Diesel 5W-40 DPF. Instant Protection From The Moment You Start.

**As tested in the industry Sequence IVA wear test.*

Application

Castrol MAGNATEC Diesel 5W-40 DPF is suitable for use in automotive diesel and gasoline engines where the manufacturer recommends an API SN/CF or ACEA C3 5W-40 lubricant including vehicles fitted with a diesel particulate filter.

Castrol MAGNATEC Diesel 5W-40 DPF is approved for use in vehicles from a number of leading manufacturers please refer to specifications and owner's hand book.

*GM dexos2TM: supersedes GM-LL-B-025 and GM-LL-A-025 : GB2F0126082

Advantages

Castrol MAGNATEC Diesel 5W-40 DPF:

- Synthetic Diesel technology to provide increased protection in high and low temperature applications;
- Provides continuous protection for all driving conditions, styles and temperatures;
- Delivers superior performance under extreme cold start up conditions

Castrol MAGNATEC Diesel DPF 5W-40 - suitable for TDI, DI, Inter-cooled, Turbocharged engines, CRDI engines.

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC Diesel 5W-40 DPF
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	6200
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	76
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C3

API SN/CF

Meets Fiat 9.55535-S2

Meets Ford WSS-M2C917-A

GMdexos2™*

MB-Approval 229.31

VW 505 00/ 505 01

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC Diesel 5W-40 DPF

20 Mar 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk