



## Radicool

Summer coolant and antifreeze.

### Description

Castrol Radicool is a concentrated engine coolant for use in both petrol and diesel engines with aluminium or cast iron engines. This coolant can be mixed using 33% concentration with purified water to give frost protection to -18 deg C, however it is recommended to use a 50% dilution to provide optimum corrosion protection and freeze protection down to -36 deg C. At these concentrations this coolant will provides year round protection. To maintain optimum performance this product should be replaced after 1 year

### Application

Castrol Radicool is a mixture of monoethylene glycol and selected chemical agents. It contains no nitrites, amines or phosphates. Because it contains no phosphate, the problems of deposits in some modern performance engines are reduced.

Castrol Radicool provides -

- protection aganist hard water
- effective engine cooling without boiling;
- protection against corrosion of the alloys used in the cooling system of modern vehicles;
- compatibility with conventional seal and hose materials used in engine cooling systems;
- protection against cavitation corrosion;
- efficient lubrication of water pumps
- contains bittering agent

In the majority of cases, coolants are not compatible and should not be mixed with other coolants unless directed by the equipment manufacturer. If using Castrol Radicool for the first time, ensure that the cooling system has been adequately flushed with clean water before use.

#### Storage

Castrol Radicool has a shelf life of 2 years when stored in air tight containers at a maximum temperature of 30°C. In warm climates containers should not be stored outside in direct sunlight. It can be stored in mild steel lacquer lined or HDPE containers .Galvanised containers and handling equipment should be avoided.

## Typical Characteristics

Name	Method	Units	Castrol Radicool
Density @ 20C	ASTM D1122	g/ml	1.12
Appearance	Visual	-	bright clear fluid
pH, Aqueous Solution (50%)	ASTM D1287	pH	7.5
Foam, Tendency of Engine Coolants	ASTM D1881	ml	50 max
Foam, break time	ASTM D1881	seconds	5 max
Water	ASTM D1123	% wt	5 max
Boiling Point of Engine Coolants	ASTM D1120	°C	160 min

## Product Performance Claims

ASTM D3306  
BS 6580:2010  
JIS K2234

Radicool  
28 Jul 2016  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square, P.O. Box 1699, Dubai, United Arab Emirates  
Technical / Customer Service: +9714-3317999  
[www.bp.com](http://www.bp.com)