

Castrol Activ ESSENTIAL SAE 40

Essential Engine Protection for a Trouble-Free Ride

Description

Bike maintenance can be expensive, but poor engine oils can risk the essential protection of the engine and hurt the value of the bike.

Application

Castrol Activ ESSENTIAL SAE 40 is suitable for use in bikes requiring API SF (and below) specifications.

Not suitable for motorcycles/scooters requiring a JASO spec (MB, MA, MA1 or MA2)

Advantages

Castrol Activ ESSENTIAL SAE 40 provides essential protection for the bike's engine and helps keep it clean.

Typical Characteristics

Name	Method	Units	Activ ESSENTIAL SAE 40
Density @ 15C, Relative	ASTM D4052	g/ml	0.892
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.75
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	149.4
Viscosity Index	ASTM D2270	None	98
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	226.5

Product Performance Claims

API SF

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ ESSENTIAL SAE 40

04 Aug 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn. Bhd., Registration No. 198701007157 (165875-W), Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8,
Jalan Kerinchi, 59200 Kuala Lumpur
Phone No : 03-22818181 Toll free Line: 1-800-81-6530
www.castrol.com