



Product Data

Castrol Radicool NF Premix Go

Ready to use. Cools and protects for up to 3 years.

Description

Castrol Radicool NF Premix Go is a ready to use engine coolant and antifreeze formulated using monoethylene glycol and selected additives, free from nitrites, amines, phosphates and 2-ethylhexanoic acid (Hybrid Additive Technology (HAT)).

Castrol Radicool NF Premix Go is a ready to use product and does not require further dilution with water, ensuring a year-round protection against corrosion and a freezing protection down to -37°C.

Application

Castrol Radicool NF Premix Go can be used in a wide range of aluminium and cast-iron engines and has been developed to provide total protection for modern engine radiator systems, cylinder block heads, water pumps and heat exchangers.

Castrol Radicool NF Premix Go is suitable for a broad range of car and commercial vehicle manufacturers requiring a Hybrid Additive Technology coolant. Refer to vehicle's handbook for details.

In the majority of cases, coolants of different technologies (e.g. HAT, OAT, Si-OAT) are not compatible and should not be mixed unless directed by the equipment manufacturer.

If using Castrol Radicool NF Premix Go for the first time and the previous coolant type is not known, ensure the cooling system has been adequately flushed with clean water before use.

Advantages

Castrol Radicool NF Premix Go:

- Suitable for a broad range of vehicle manufacturers
- Provides excellent protection against corrosion of all components of the cooling system
- Its phosphate-free formulation prevents the formation of deposits which can affect coolant flow
- Reduces the likelihood of wet cylinder liner pitting caused by cavitation
- Protects the entire system for up to 3 years
- Contains bittering agent

Typical Characteristics

Name	Method	Units	Castrol Radicool NF Premix Go
pH value	ASTM D1287		8.3
Color	Supplier		Blue
Appearance	Visual		Clear & Bright
Freezing Point	ASTM D3321	°C	-37

Performance

Suitable for use where following industry standards are required

ASTM D3306 (III)

ASTM D4985

Based on coolant concentrate conforming to BS 6580:2010

JASO JIS K2234:2006

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Radicool NF Premix Go

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com