



## Power 1 Racing 4T 10W-40

Race Derived Technology

### Description

Castrol POWER1 Racing 4T is specifically designed for bikers who love the exhilaration of riding on the edge.

Castrol POWER1 Racing is fully synthetic engine oil. Castrol POWER1 Racing incorporates Race Derived Technology developed by Castrol's long and successful racing association by working with the world's leading racing teams for over five decades.

This fully synthetic engine oil flows fast and stays strong, reducing internal engine friction even under the most arduous riding conditions. It has been tested and proven to deliver exceptional acceleration and power at the touch of the throttle.

The added Castrol advantage of Trizone Technology™ ensures uncompromised performance protection, its ultimate performance for extreme riding.

### Application

Castrol POWER1 Racing 4T is designed for high performance 4-stroke sports bikes to deliver optimum power and protection in all riding conditions.

It is suitable for all makes of 4-strokes bikes, both carburettor and fuel injected where API SN (and below) and JASO MA or MA2 specifications are recommended.

### Advantages

- Ultimate performance in extreme riding – oil flows fast and stays strong, reducing internal engine friction
- Tested and proven to deliver exceptional acceleration at the touch of the throttle
- Fully synthetic 4-stroke motorcycle engine oil with Trizone protection of engine, clutch and gears
- Complies with requirements of catalyst equipped engines

## Typical Characteristics

| Name                      | Method     | Units              | Power 1 Racing 4T 10W-40 |
|---------------------------|------------|--------------------|--------------------------|
| Density @ 15C, Relative   | ASTM D4052 | g/ml               | 0.8528                   |
| Appearance                | Visual     | -                  | Clear & Bright           |
| Viscosity, Kinematic 100C | ASTM D445  | mm <sup>2</sup> /s | 14.53                    |
| Viscosity, Kinematic 40C  | ASTM D445  | mm <sup>2</sup> /s | 93.5                     |
| Viscosity Index           | ASTM D2270 | None               | 162                      |
| Total Base Number, TBN    | ASTM D2896 | mg KOH/g           | 6.9                      |

## Product Performance Claims

API SN  
JASO MA2

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Power 1 Racing 4T 10W-40

29 Sep 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square , P.O. Box 1699, Dubai, United Arab Emirates  
Technical / Customer Service: +9714-3317999  
[www.bp.com](http://www.bp.com)