

Vecton 10W-40 Bioethanol SLD

Helps maximise performance

Description

Castrol Vecton 10W-40 Bioethanol SLD is a 10W-40 heavy duty engine oil designed to maximize performance in the latest Scania DC9 E02 bioethanol engines for bus operations.

Castrol Vecton 10W-40 Bioethanol SLD can also be used in older bioethanol engines from Scania. NB: Not for use in diesel fuelled heavy duty vehicles

Typical Characteristics

Name	Method	Units	Vecton 10W-40 Bioethanol SLD
Density @ 15C	ASTM D4052	g/ml	0.874
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.7
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	90
Viscosity Index	ASTM D2270	None	154
Ash, Sulphated	ASTM D874	% wt	0.8
Total Base Number, TBN	ASTM D2896	mg KOH/g	5.8
Pour Point	ASTM D97	°C	-39

Product Performance Claims

Scania Bioethanol engine oil approved

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Vecton 10W-40 Bioethanol SLD

04 Dec 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com