



PRODUCT DATA

Castrol Transmax™ Import Multi-Vehicle Automatic Transmission Fluid (ATF)

Castrol Transmax™ Import Multi-Vehicle Automatic Transmission Fluid is for use in most Honda, Toyota, Nissan and other imported vehicles. It exceeds the requirements of the JASO-1A performance standard created by Japanese Automobile Manufacturers. This standard is recognized by Japanese OEMs in certifying ATF for use in their vehicles.

Features and Benefits

- Enhanced friction durability for smooth transmission performance
- Exceptional high temperature protection to effectively resist fluid oxidation
- Superb low temperature fluidity for cold weather shifting

Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-IIIH, MERCON® or MERCON® V type ATF is specified

Industry Specifications and OEM Approvals

- Meets or exceeds General Motors DEXRON®-IIIH requirements
- Meets or exceeds Ford MERCON® V and Ford MERCON® requirements
- MERCON® V approved and licensed by Ford Motor Company
- Meets or exceeds JASO-1A requirements

Recommended for use in vehicles as indicated below:

Manufacturer	Specification
Acura	ATF-Z1 (except in CVTs)
Chrysler	ATF+3®, ATF+2®, , ATF+®
Ford	MERCON V®, MERCON®, XT-9QMM5
General Motors	DEXRON®-III H, II-D, II, DEXRON®; 9986195; Type A, Suffix A (TASA)
Honda	ATF-Z1, ATF DW-1, (except in CVTs)
Hyundai	SP-II, SP-III
Idemitsu	K17
Infiniti	Matic-D, Matic-J, Matic-K
Isuzu	Genuine
Kia	All specifications
Lexus	Type T, T-III, T-IV
Mazda	ATF M-V



Mitsubishi	Diamond SP-II, SP-III
Nissan	Matic-D, Matic-J, Matic-K
Saab	Transmax J
Subaru	All specifications
Toyota	Type T, T-III, T-IV
Volvo	All specifications
Various (Aisin-Warner transmissions)	JWS-3309
Various European Vehicles where DEXRON®-IIIH or Mercon are called For	DEXRON®-IIIH, Mercon

Note: Castrol does not recommend Import Multi-Vehicle ATF for use in continuously variable transmissions (CVTs) or where Ford Type F or GM DEXRON®-VI fluids are required.

Typical Properties*

Test	Method	Typical Results
Viscosity at 40 °C, cSt	ASTM D-445	36.6
Viscosity at 100 °C, cSt	ASTM D-445	8
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	10,500
Pour Point, °C (°F)	ASTM D-97	-48(-54)
Flash Point, °C (°F)	ASTM D-92	208(406)
Specific Gravity, 60 °F	ASTM D-1298	0.862
Pounds per Gallon	ASTM D-287	7.17

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

Part Numbers and UPCs

Packaged Goods

Case Size	6/1 QT	3/1 GA
Case Part No.	06814	03521
Bottle/ Unit UPC	0-79191-00143-1	0-79191-00521-7
Case UPC	0-79191-06814-4	0-79191-03521-4

Bulk/Drum

Unit Size	16 GA DRUM	55 GA DRUM	BULK
Part No.	16001	55455	0455



Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: 1,800,462.0835
Email: contactus@bp.com
©2011 BP Lubricants USA Inc. All rights reserved.

www.castrol.com/us