



Castrol EDGE Professional 5W-40

Stronger Under Pressure

Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. This means the oil has to be stronger to reduce friction and protect the engine.

Castrol EDGE Professional is micro-filtered and CO₂ neutral according to the highest global standard*. It provides the strength to help maximise your vehicles performance.

Castrol EDGE Professional: stronger under pressure.

** in accordance with the BSI PAS 2060 specification*

Application

Castrol EDGE Professional 5W-40 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an API SM/CF or earlier specification 5W-40 lubricant.

Castrol EDGE Professional is approved by TATA Motors and Maruti Suzuki. Please refer to your owners handbook.

Advantages

Castrol EDGE Professional 5W-40 is the natural choice for drivers who demand maximum engine performance from today's sophisticated vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE Professional 5W-40:

- Independently tested at the highest standards
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Proven performance across a variety of driving conditions and temperatures

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional 5W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.0
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	5940
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	85
Viscosity Index	ASTM D2270	None	171
Ash, Sulphated	ASTM D874	% wt	1.0
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	213

Product Performance Claims

API SM/CF

TATA and Maruti Suzuki approved

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional 5W-40

14 Mar 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com