



Castrol Fork Oil 20W

Motorcycle Suspension Oil

Description

Castrol Fork Oil 20W is an advanced mineral based suspension fluid designed to provide superior damping performance in all on and off road suspensions.

Application

Castrol Fork Oil is suitable for suspension damper units for on and off road motorcycles (including motocross) and road machines from main Japanese, Eastern and European OEMs.

Advantages

Castrol Fork Oil provides the following benefits:

- improved damping performance over a wide range of temperatures;
- fast air release for anti-fade performance;
- wear protection of suspension components;
- protection against corrosion of all the internal parts;

Typical Characteristics

Name	Method	Units	Fork Oil 20W
Density @ 15C, Relative	ASTM D1298	g/ml	0.88
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	68
Pour Point	ASTM D97	°C	-36
Viscosity Index	ASTM D2270	None	140
Flash Point, PMCC	ASTM D93	°C	220
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Fork Oil 20W

07 Jun 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com