



POWER1 Scooter 2T

THE OIL THAT OFFERS OUTSTANDING PERFORMANCE AND PROTECTION.

Description

New Castrol POWER1 is engineered to deliver outstanding performance and protection.

Application

- Castrol POWER1 Scooter 2T exceeds JASO FD and ISO-L-EGD.
- It is recommended for all 2-Stroke scooters.

Advantages

Castrol POWER1 Scooter 2T with:

- Power Sustain Formula™ keeps engine clean
- Low-ash formulation helps to reduce spark plug fouling
- Excellent high temperature detergency
- Compatible with modern catalytic converters

Typical Characteristics

Name	Method	Units	Castrol POWER1 Scooter 2T
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44.3
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.6
Flash Point, PMCC	ASTM D93	°C	75
Viscosity Index	ASTM D2270	None	145

Performance

ISO-L-EGD

JASO FD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 Scooter 2T

31 Oct 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com