



## Castrol Activ 4T 20W-40

Continuous Protection

### Description

A motorcycle engine is at risk of damage when it's warming up, running normally and even when turned off. There are over 10 million instances per month where a motorcycle-engine could be damaged.

New Castrol Activ 4T 20W-40 has improved Actibond™ molecules that cling firmly to the engine to provide Continuous Protection through all stages of the ride, and beyond: Start up, Running and Stop.

### Application

Castrol Activ 4T 20W-40 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO MA-2 and MA specifications are recommended.

### Advantages

Castrol Activ 4T 20W-40 contains Actibond™ molecules that firmly cling to engine parts and:

- Provide 75% better wear protection\*\* during start-up
- Fight deposits and provide superior engine cleanliness during running
- Provide excellent corrosion protection, even when the engine is off

New Castrol Activ 4T 20W-40 delivers 50% better protection\*

\*vs industry limits for API SL and JASO MA2 specifications

\*\*vs reference API SL oil in Seq IVA test

## Typical Characteristics

Name	Method	Units	Activ 4T 20W-40
Density	ASTM D4052	g/ml	0.8879
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.0
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	124.10
Viscosity Index	ASTM D2270	None	110
Pour Point	ASTM D97	°C	-18
Flash Point, PMCC	ASTM D93	°C	>185

## Product Performance Claims

API SL  
JASO MA-2

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T 20W-40  
22 Sep 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Philippines Inc, 32nd Floor, LKG Tower, 6801 Ayala Avenue, Makati City, Philippines 1226  
Technical Advice Line: +63 2 8841478 Customer Service: +63 2 8841478 Fax No. +63 2 8841911  
[www.castrol.com](http://www.castrol.com)