



Product Data

MTX Full Synthetic 75W-140

Fully synthetic transmission lubricant

Description

Castrol MTX Full Synthetic 75W-140 is a fully synthetic transmission lubricant for 2T and 4T On and Off-Road motorcycles.

Application

Castrol MTX Full Synthetic 75W-140 is suitable for use in high performance 2T and 4T transmission with wet or dry clutch systems and for final drives.

Advantages

- 75W-140 .
- Motorcycle gear and final drive oil.
- Grand Prix Series.
- For 2T and 4T high performance motorcycles - suitable for wet clutch systems.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.87
Viscosity, Kinematic 100C	ASTM D445	mm²/s	24.99
Viscosity, Kinematic 40C	ASTM D445	mm²/s	182.2
Viscosity Index	ASTM D2270	None	170
Pour Point	ASTM D97	°C	-54
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	147000

Product Performance Claims

API GL-5

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

MTX Full Synthetic 75W-140

23 Dec 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com