



Product Data

ON EV Transmission Fluid W2

EV Transmission Fluid

Description

Castrol ON EV Transmission Fluid W2 is a full synthetic, high performance, high efficiency fluid for transmissions with wet e-Motors, i.e., where the e-motor operates immersed in the EV Transmission Fluid. It is an advanced EV Transmission Fluid that helps extend the life of the drivetrain system and go further¹ on a single charge. This next generation transmission fluid has specially developed, low viscosity technology that delivers low electrical conductivity, enhanced system protection and helps the e-motor run cooler enabling it to operate at high efficiency.

*¹vs mass market EV factory fill fluid *Castrol EV Fluids benefits are demonstrated in bespoke testing and development.*

FOR PROFESSIONAL USE ONLY

Advantages

1. Outstanding dielectric properties:
 - o low conductivity
 - o high resistance
 - o high breakdown voltage
2. Excellent copper corrosion protection
3. Excellent pumpability at low operating temperatures
4. Exceptional cold flow properties
5. Excellent thermal and oxidative stability
6. Exceptional temperature reduction through reduced friction
7. Very good gear protection
8. Excellent thermal properties

**please check with your vehicle manufacturer for the right type of fluid for your electric vehicle*

Typical Characteristics

Name	Method	Units	ON EV Transmission Fluid W2
SAE Grade		-	75W
Density @ 15C, Relative	ASTM D4052	g/ml	0.851
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	5.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	18
Viscosity Index	ASTM D2270	None	300
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	2200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	234
Foam Tendency , Seq I / II / III	ASTM D892	ml	0 / 10 / 0

ON EV Transmission Fluid W2

23 Oct 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com