



GTX Ultraclean 5W-20

No oil keeps engines cleaner

Description

Castrol® GTX® ULTRACLEAN is one of the world's most trusted engine oils. The modern world creates difficult challenges for engines. Poor fuel quality, heat and tough driving conditions can all lead to sludge that potentially shortens engine life. Sludge is a sticky deposit that builds up in an engine's oil-ways and it can prevent the oil from protecting the engine. Castrol® GTX® ULTRACLEAN with synthetic technology - and its proprietary sludge buster - is our cleanest GTX® ever. Its unique Double Action formula cleans away old sludge** and protects against new sludge formation, giving you more control over today's challenging conditions.

Provides superior protection in gasoline direct injection engines (including but not limited to GDI, FSI, SIDI, EcoBoost – check your owner's manual for details).

Application

Exceeds manufacturer's warranty requirements for applications requiring API Plus SN/SM/SL/SJ and ILSAC GF-5/GF-4/GF-3

Castrol GTX Ultraclean 5W-20 Meets - Ford WSS-M2C930-A / Ford WSS-M2C945-B1 specifications.

Advantages

Castrol GTX Ultraclean provides:

- 45% superior sludge protection compared to tough industry standards*
- Advanced protection against viscosity and thermal breakdown
- Superior protection against high temperature deposits
- Premium quality base oils and anti-wear additives that help extend the life of your engine

* 45% cleaner than the industry standard as measured in the VH Sludge test

** When tested in engines with high level of sludge

Typical Characteristics

Name	Method	Units	Castrol GTX Ultraclean 5W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.859
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.6
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5343
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	51
Viscosity Index	ASTM D2270	None	148
Ash, Sulphated	ASTM D874	% wt	0.78
Flash Point, COC	ASTM D92	°C	231

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

GTX Ultraclean 5W-20

24 Jul 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com