



Product Data

Syntilo 9954

High Performance Synthetic Cutting and Grinding Fluid

Description

Castrol Syntilo 9954 is a high performance synthetic cutting and grinding fluid for ferrous metals. This oil-rejecting fluid performs the most difficult operations with superior performance. Syntilo 9954 performs exceptionally well as a replacement for straight cutting oils in applications such as gun-drilling and gear hobbing. Syntilo 9954 is a clean fluid capable of reducing overall production costs while satisfying the most critical machining requirements.

Application

- Incorporates a combination of surfactant technologies that provide increased lubrication versus conventional synthetic metalworking fluids
- Rejects tramp oils to the surface of the fluid for easy skimming
- Low foaming in all water conditions
- Inhibits microbial growth to extend fluid life in central systems and individual sumps
- Prevents bi-metallic corrosion and is safe to use in equipment with copper, brass or bronze components

Typical Characteristics

Name	Method	Units	Value
Appearance of Concentrate	Visual	-	Clear yellow fluid
Appearance of Dilution	Visual	-	Clear to slightly yellow fluid
pH of Dilution	-	@ 5%	8.0 - 8.8
Specific Gravity	CN-TM-086	@ 60°F (16°C)	1.083 - 1.093
Bulk Density	-	lbs/gal	8.9
Chlorine	-	-	No
Nitrites	-	-	No
Phenols	-	-	No

Recommended Concentrations

Grinding: 3 - 6%
Machining: 5 - 10%

Concentration Control

% Concentration	Refractometer Reading
3.0	2.2
5.0	3.9
7.0	5.5
10.0	7.1

User Advice

Syntilo 9954 is recommended for machining and grinding of ferrous metals, including stainless steels and alloys. Consult a Castrol representative for questions regarding compatibility.

Syntilo 9954
12 Jan 2018
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html