



React SRF Racing

Racing Brake Fluid

Description

Castrol React SRF Racing is a high performance brake fluid of special value in competitive motor sport where extreme braking conditions are encountered. It is an exclusive Castrol product registered under patents in many countries. Castrol React SRF Racing meets US Federal Standards FMVSS 116 DOT 3 and DOT 4, ISO 4925, JASO JIS K2233 and current SAE J 1703 specifications.

Application

Castrol React SRF Racing has an exceptionally high dry boiling point, typically 325°C, making it ideal for use under arduous braking conditions such as racing or rallying.

Castrol React SRF Racing has a very high vapour lock point (the more important measure of high temperature performance under actual braking conditions), and has the additional advantage of sustaining high vapour lock point characteristics during its service life.

In order to achieve the optimum benefits in such applications, advanced materials have been employed in a unique and patented Castrol formulation.

The properties of this formulation are such that in order to derive maximum benefit the use of Castrol React SRF Racing should be restricted to not more than eighteen months before draining and refilling.

Advantages

Castrol React SRF Racing is suitable for all disc and drum brake systems with the exception of those for which mineral oil is prescribed. It is miscible with all conventional fluids meeting US Federal Standards FMVSS 116 DOT 3 and DOT 4, ISO 4925 and current SAE J 1703 and J1704. However, mixing with conventional brake fluids will merely reduce the higher quality of Castrol React SRF Racing and therefore recommended that conventional brake fluids be drained from the system before flushing and re refilling.

It is recommended that this fluid is changed every 18 months to maintain it's exceptionally high vapour lock performance.

Typical Characteristics

Name	Method	Units	Castrol React SRF Racing
Density @ 20C, Relative	IP 160	g/ml	1.066
Appearance	Visual	-	Yellow, Clear & Bright
ERBP (Equilibrium Reflux Boiling Point)	ASTM D1120	°C	320
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	270
Water	ASTM D1123	% wt	0.15
Viscosity at -40 °C	ASTM D445	mm ² /s	1300
Viscosity at 100°C	ASTM D445	mm ² /s	3.5

Product Performance Claims

FMVSS 116 DOT 3
FMVSS 116 DOT 4
ISO 4925 (Class 4)
SAE J1703
JIS K2233 (Class 4)

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

React SRF Racing
10 Apr 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au