

ON EV Transmission Fluid W5

EV Transmission Fluid

Description

Castrol ON EV Transmission Fluid W5 is a full synthetic, high performance, high efficiency fluid for transmissions with wet e-Motors, i.e., where the e-motor operates immersed in the EV Fluid. It is an advanced EV Transmission Fluid that helps extend the life of the drivetrain system and go further¹ on a single charge. This next generation transmission fluid has specially developed, low viscosity technology that delivers low electrical conductivity, enhanced system protection and helps the e-motor run cooler enabling it to operate at high efficiency.

*¹vs mass market EV factory fill fluid *Castrol EV Fluids benefits are demonstrated in bespoke testing and development.*

FOR PROFESSIONAL USE ONLY

Advantages

1. Outstanding di-electrical properties:
 - low conductivity
 - high resistance
 - high breakdown voltage
2. Very good copper corrosion protection
3. Excellent pumpability at low operating temperatures
4. Exceptional cold flow properties
5. Excellent thermal and oxidative stability
6. Exceptional temperature reduction through reduced friction
7. Excellent gear protection
8. Excellent thermal properties

**please check with your vehicle manufacturer for the right type of fluid for your electric vehicle*

Typical Characteristics

Name	Method	Units	ON EV Transmission Fluid W5
SAE Grade		-	75W
Density @ 15C, Relative	ASTM D4052	g/ml	0.836
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	4.3
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	19
Viscosity Index	ASTM D2270	None	139
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	4400
Pour Point	ASTM D97	°C	- 48
Foam Tendency, Seq I / II / III	ASTM D892	ml	0 / 10 / 0
Shear Stability (KRL) – CEC L-45-99 % Loss in KV100 after 20 Hours	ASTM D445	%	< 2

ON EV Transmission Fluid W5

19 Dec 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com