



CRB Viscus 25W-60

.For a long and healthy engine life

Description

Castrol CRB Viscus 25W-60 is a multi-purpose, heavy duty diesel engine oil. It is suitable for use in naturally-aspirated, turbocharged or supercharged diesel engines that use a broad range of fuel qualities.

Advantages

Castrol CRB Viscus 25W-60 with the exclusive Viscus additive system provides the highest viscosity in the market and protection at high engine temperatures to encourage long and healthy engine life.

Castrol CRB Viscus 25W-60 delivers protection 3 ways by:

- Providing 23% greater viscosity than 25W-50 oils*
- Helping to preserve peak oil pressure and horsepower.
- Helping to prevent seal leakage to minimise oil consumption

*Result compared to typical 25W-50 oils

Typical Characteristics

Name	Method	Units	CRB Viscus 25W-60
Density @ 15C	ASTM D4052	g/ml	0.900
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	23.2
Viscosity, CCS -10C (25W)	ASTM D5293	mPa.s (cP)	9000
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	243
Viscosity Index	ASTM D2270	None	118
Ash, Sulphated	ASTM D874	% wt	0.95
Total Base Number, TBN	ASTM D2896	mg KOH/g	7.3
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	220

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

API CF-4

User Advice

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

Additional Information

Meets API CF-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Viscus 25W-60

21 Sep 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com