



## EDGE Professional V 0W-20

Strength for Maximum Performance

### Description

Today's technology has allowed car manufacturers to produce smaller, yet more powerful and efficient engines with the aim to deliver increased fuel economy, reduce emissions and high performance. Downsizing, turbo charging and advanced engine designs like direct fuel injection and variable valve timing have now almost doubled engine pressures putting more stress on the oil. The oil is now operating under higher temperatures and having to withstand pressures in excess of 10 tons of pressure per square centimeter in areas like the cam and follower.

### Application

Specially engineered for Volvo vehicles.  
See product performance claims for a complete list of approvals.

### Advantages

Exclusively for new car dealerships, Castrol EDGE Professional is boosted with titanium FST doubles its film strength helping prevent oil film breakdown and reducing friction to help maximize engine performance. Castrol EDGE Professional is certified carbon neutral and micro-filtered to highest quality standards.

For more information visit [www.castrol.com/us](http://www.castrol.com/us) or contact your Castrol Sales Representative at 1-888-castrol.

## Typical Characteristics

Name	Method	Units	Typical values
Density @ 15C, Relative	ASTM D4052	g/ml	0.8421
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	8.84
Viscosity, CCS -35C	ASTM D5293	mPa.s (cP)	4600
Viscosity, MRV / Yield Stress -40C (0W)	ASTM D4684	mPa.s (cP)	14000
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	47.09
Viscosity Index	ASTM D2270	None	171
Noack Volatility	CEC L-40-A-93	% Loss	11.9
Gelation Index	ASTM D5133	-	6.0
Viscosity, HTHS 150C	CEC-L-14-A-97	cP	2.8
Pour Point	ASTM D97	°C	-54
Flash Point, PMCC	ASTM D93	°C	206

## Product Performance Claims

ACEA A1/B1

Volvo VCC RBS0-2AE

EDGE Professional V 0W-20

25 Oct 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)